

# 印刷用ステンレススクリーン（ノーマル/非カレンダー加工品）規格表

大阪メッシュ株式会社

	コードNo.	メッシュ数	線径	開き目	空間率	紗厚 [μm]		透過体積	材質	紗幅 [cm] および在庫				
	メッシュ線径	[本/インチ]	[μm]	[μm]	[%]	公称	厚み範囲	[ / ]	SUS	100	122	153	200	250
DX & GTS	40-160	40	160	475	56	320	300~320	179.2	316	D	D			
	50-140	50	140	368	52	280	265~280	145.6	316	D	D			
	60-140	60	140	283	45	280	260~280	126.0	316	D	D			
	60-120	60	120	303	51	240	230~245	122.4	316	D	D			
	70-70	70	70	293	65	140	135~143	91.0	304		G			
	80-120	80	120	198	39	240	235~245	93.6	316	D	D			
	80-100	80	100	218	47	200	195~205	94.0	316	D	D			
	80-50	80	50	268	71	100	95~104	71.0	304		G			
	100-100	100	100	154	37	210	195~215	77.7	316	D	D			
	100-50	100	50	204	65	100	98~103	65.0	304		G			
	100-30	100	30	224	78	59	57~61	46.0	304		G			
	120-80	120	80	132	39	170	155~170	66.3	316	D	D	D		
	145-55	145	55	120	47	110	105~115	51.7	304		G			
	150-65	150	65	104	38	131	128~135	49.8	316		D	D		
	150-60	150	60	109	42	120	115~122	50.4	316	D	D	D		
	165-50	165	50	104	46	100	97~105	46.0	316	D	D			
	165-45	165	45	109	50	90	88~93	45.0	304	G	G	G		
	165-35	165	35	119	60	72	70~75	43.2	304	G	G	G		
	180-50	180	50	91	42	100	98~105	42.0	316	D	D	D		
	180-45	180	45	96	46	90	88~93	41.4	316		G			
	200-50	200	50	77	37	100	98~103	37.0	316			D		
	200-40	200	40	87	47	80	79~83	37.6	304	G	G	G	G	G
	200-30	200	30	97	58	60	58~64	34.8	304	G	G			
	230-35	230	35	75	47	70	68~73	32.9	304	G				
	250-40	250	40	62	37	80	79~83	29.6	304	G	G	G		
	250-35	250	35	67	43	70	68~73	30.1	304	G	G	G	G	G
	250-30	250	30	72	50	60	59~63	30.0	304	G・S	G	G		
	250-28	250	28	74	53	56	54~58	29.7	304	G	G			
	270-35	270	35	59	40	70	68~73	28.0	304	G				
	300-30	300	30	55	42	69	66~69	29.0	304	G	G			
325-35	* 325	35	43	30	84	82~86	25.2	304	G					
325-28	325	28	50	41	64	60~66	26.2	304	G	G	G	G	G	
325-18	325	18	60	59	38	36~40	22.4	304		G				
350-25	350	25	48	43	52	50~54	22.4	304	G	G				
400-30	* 400	30	34	28	74	71~77	20.7	304	G					
400-23	400	23	41	41	54	52~56	22.1	304	G	G	G	G	G	
400-18	400	18	46	51	38	36~42	19.4	304	G	G	G			
500-25	* 500	25	26	26	58	55~62	15.1	304	G					
500-19	500	19	32	39	41	39~43	16.0	304	G	G				
500-18	500	18	33	42	38	36~40	16.0	304	G	G				

	コードNo.	メッシュ数	線径	開き目	空間率	紗厚 [μm]		透過体積	材質	紗幅 [cm] および在庫				
	メッシュ線径	[本/インチ]	[μm]	[μm]	[%]	公称	厚み範囲	[ / ]	SUS	100	122	153	200	250
SG	250-25	250	25	77	57	53	51~55	30.2	304		S	S		
	250-23	250	23	79	60	46	45~48	27.6	304			S		
	250-20	250	20	82	65	42	40~44	27.3	304		S			
	325-23	325	23	55	50	51	49~55	25.5	304	S	S	S		
SH	500-18	500	18	33	42	38	36~40	16.0	304	H				
	500-16	500	16	35	47	33	31~35	15.5	304	H				
	640-15	640	15	25	39	34	32~36	13.3	304	H				

RX	230-25	230	25	85	60	56	54~58	33.6	304	R	R	R	R	R
	290-20	290	20	68	60	46	44~48	27.6	304	R	R	R	R	R
	325-16	325	16	62	63	35	32~38	22.1	304	R				R
	360-16	360	16	55	60	35	32~38	21.0	304	R				
	380-14	380	14	53	63	31	29~33	19.5	304	R				
400-20	* 400	20	44	47	46	44~48	21.6	304					R	

備考) 上記「メッシュ数」欄の数字の前に\*があるものは綾織です。

2007.08.17 現在